



# ColdFAST

COLDFAST U 778S



# Technical specifications

## ColdFAST U 778S

### COLDFAST U 778S

Model	Type of Construction	Upright	
	Capacity (l)	778	
	Inner Dimensions (W x D x H) mm	865 x 696 x 1286	
	Outer Dimensions (W x D x H) mm	1205 x 1025 x 1955	
	Package Dimensions (W x D x H) mm	1320 x 1155 x 2171	
	Net / Gross Weight (kgs)	365 / 462	
Performance	Cooling Performance (°C)	-86	
	Temperature Range (°C)	-40 ~ -86	
	Ambient Temperature (°C)	16 ~ 32	
	Climate Class	N	
	Sound Level (dB(A))	44	
	Controller	Microprocessor	
	Display	10" HD Intelligent Touch Screen	
Refrigeration	Compressor	2 pcs (Inverter technology)	
	Cooling Mode	Direct Cooling / Double Cascade	
	Defrost Mode	Manual	
	Refrigerant	HC	
	Insulation Thickness (mm)	130	
	Construction	External Material	Cold Rolled Steel Sheet
Inner Material		Stainless Steel	
Shelves		3 (Stainless Steel)	
Inner doors		2 (optional: 4)	
Door Lock		Yes, with key	
Padlock		Yes	
Access Test Port		3 pcs. Ø 25 mm	
Casters		4 + (2 leveling feet)	
Data Logging / Time / Duration		USB / Record Every 5 Minutes / 10 Years	
Backup Battery		Yes	
WiFi		Yes	
Alarm		Temperature	High / Low Temperature, High Ambient Temperature
		Electrical	Power Failure, Low Battery
	System	Sensor Failure, Main Board Communication Error, Condenser Overheating, Door Ajar	
Electrical Data	Power Supply (V/HZ)	110 - 230 / 50 - 60	
	Rated Power (W)	790	
	Current Consumption (KWh/24h) at 20°C ambient room temperature	8,2	
	Electrical Current (A)	7,5	
Accessories	Standard	RS485, Remote Alarm Contact	
	Options	Chart-Recorder, CO <sub>2</sub> -Backup-System, Thermal-Printer, Bluetooth-Printer, Finger-Print or RFID-Chip, Racks, Boxes & Tubes	

The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading. There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.