




Three-layer septa for GC inlet

Three-layer septa for GC inlet

Low density silicone was sandwiched between two high density silicone layers. Working temperature max. 200 °C.



Code	Description	Packaging
LLG09221801	Three-layer septa,diam. 6,35mmpack o/12	12 pz
LLG09221802	Three-layer septa,diam. 8,00mmpack o/12	12 pz
LLG09221803	Three-layer septa,diam. 9 mm, pack o/12	12 pz
LLG09221804	Three-layer septa,diam. 9,50mmpack o/12	12 pz
LLG09221805	Three-layer septa,diam.11mm, pack of/12	12 pz
LLG09221806	Three-layer septa,diam. 12,70mmpack /12	12 pz
LLG09221807	Three-layer septa,diam. 11,00mmpack /12	12 pz
LLG09221808	Three-layer septa,diam. 16,00mmpack /12	12 pz
LLG09221809	Three-layer septa,diam. 12 mm, pack /12	12 pz



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

