

**Conductivity meter FiveGo F3**

Mettler-Toledo Online

Conductivity meter FiveGoä F3

Portable conductivity meter for field work.

- Measurement made easy: A large, well-structured display, intuitive button arrangement and simple menu ensure measurements can be performed in just a few clicks
- Ergonomic design for one handed operation: Thanks to its ergonomic design, handling the FiveGo is a comfortable experience. The foldable stand provides optimal viewing on flat surfaces
- IP67 Water and dustproof: The IP67 waterproof protection makes the FiveGo portables able to withstand wet and demanding environments

Supplied with:

F3-Meter: Meter only

F3-Standard kit: Meter with LE703 sensor

F3-Field kit: Meter with LE703 sensor, carrying case

Specifications**Conductivity****Measuring range:****Resolution:****Accuracy:**

0.00 $\mu\text{S}/\text{cm}$ $\frac{1}{4}$ 200 mS/cm

Automatic range

± 0.5 % of the measured value

Temperature**Measuring range:****Resolution:****Accuracy:**

0 ... 100 °C

0.1 °C

± 0.5 °C

TDS (Total Dissolved Solids)**Measuring range:****Resolution:**

0.01 mg/l $\frac{1}{4}$ 200 g/l

Automatic range

Temperature compensation: Linear 0.00 ... 10.00 %/°C,



reference temperature 20 and 25 °C
Calibration: 1 point, 3 predefined standards
Memory size: 200 measurements, current calibration
Dimensions (W x D x H): 188 x 77 x 33 mm
IP code: IP 67 (meter + sensor)

Code	Description	Packaging
LLG06280115	Conductivity meter FiveGo F3, Type F3-Meter	1 pz
LLG06280116	Conductivity meter FiveGo F3, Type F3-Standard kit	1 pz
LLG06280117	Conductivity meter FiveGo F3, Type F3-Field kit	1 pz





CARLO ERBA Reagents S.A.S.
Chaussée du Vexin – 27106 Val
de Reuil cedex
N° TVA: FR 63391048824
Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
Reagents operates with
a Certified Quality
Management System

